

AMENDMENTS TO THE SPECIFICATION

Please replace the paragraph beginning on page 11, line 28, with the following rewritten paragraph:

-- The conveying device 710 comprises a base 711, a plurality of transferring devices 712, a plurality of positioning devices 713, a plurality of retainers 714 and a plurality of fixtures 715. The base 711, provided with a slot 7111, is used for the fixtures 715 disposing thereupon. Each of the transferring devices 712 corresponds to a dispenser 720 and comprises a cam 7121 and a rod 7122. Each of the cams 7121 is ~~rotatably~~ rotatably disposed at the base 711. Each of the rods 7122 is connected to a cam 7121 at one end and abuts the fixture 715 through the slot 7111 at the other end. The rod 7122 moves a fixture 715 by the rotation of the cam 7121 from a position below the corresponding dispenser 720 to a position below an adjacent dispenser along the axis X. The positioning devices 713, corresponding to a dispenser 720, are disposed at the base 711 and used for pushing the fixture 715 into a predetermined position on base 711. Three retainers 714, disposed on the base 711, cooperate with a corresponding positioning device 713 by abutting the ~~substrate 730~~ fixture 715 to locate the fixture 715 at the predetermined position on the base 711. Each of the fixtures 715, disposed on the base 711, is used for receiving and supporting the substrate 730. --